



BUILDING SHELL TECHNOLOGY











Rotary mixer AOX-S

Lump free and quickly mixed



With Collomix at the pool position

-  **Compact automatic mixer for a very wide range of materials**
-  **With high speed mixing tool (-750 rpm) and counter rotating mixing bucket (65 l.) for a mixing without clumps**
-  **The rim and the bottom scraper guarantee a very efficient mixing and at the same time avoid any sedimentation of unmixed material inside the bucket**
-  **Two removable mixing tools allow the mixing of different levels of viscosities and densities.**
-  **Compact design and light weight allow high labor mobility**
-  **For the bucket transportation a dolly is available as accessory**
-  **Ideal for thin bed mortar, leveling compounds, adhesive, coverings, mortar, etc**
-  **The practical helper for mason, floor tiler, floorer, painter, renovators, ...**

Pointing mortar



Heat insulation adhesive



Tile adhesive



Thin-bed mortar



Filler



Epoxy screed



Material (weight without added water):	DLX	KR
Slightly moist concrete with grain size of -8 mm (30 l)	-	+
Concrete with max. grain size of 8 mm (30 l)	-	+
Cement screed (35 l)	-	+
Universal mortar (40 l)	-	+
Gypsum-lime mortar (35 l)	-	+
Light wall mortar (25 l)	-	+
Cement stucco (40 l)	+	+
Gypsum plaster (40 l)	+	+
Loam plaster without fiber (40 l)	+	+
Heat-insulating plaster (30 l)	-	+
Mortar for natural stone slabs (30 l)	-	+
2-component slab pointing mortar (-1,2 mm, 30 l)	+	+
Middle-bed mortar (25 l)	-	+
Tile adhesives (flexible mortar, 25 l)	-	+
Pointing mortar (25 l)	+	+
Pouring screed (40 l)	+	+
Soft/spreading types of mortar (40 l)	+	+
Thin-bed mortar, cement for concrete precision blocks (30 l)	+	+
Creamy types of plaster (40 l)	+	+
Adhesive grouting compounds as backing for plaster (30 l)	+	+
Tile adhesives (25 l)	+	+
Pointing mortar (25 l)	+	+
Joint cements (30 l)	+	+
Adhesive grouting compounds as backing for panels/tiles (30 l)	+	+
2-component sealing grouting compounds (25 l)	+	+
Leveling compounds (25 l)	+	+
2-component epoxy-resin and sand mix (30 l)	+	+



TECHNICAL DATA:

Mixing volume:	max. 40 l.	Item no. AOX-S:	37.123
Size of mixing tub:	65 l.	Item no.-mixing tool DLX	70.149
Power rating of tube drive:	1,0 kW / 230 V	Item no.-mixing tool KR	70.151
RPM of mixing mechanism:	750 rpm	Accessory	
RPM of tube drive:	18 rpm	Item no. mixing tub 65 l:	60.403
Weight:	51 kg	Item no. trolley 65 l tube:	70.183
Dimensions:	60 x 82 x 87 cm		



Collomix GmbH
Daimlerstraße 9
85080 Gaimersheim
Deutschland

Collomix Norge:
Askø Murerverktøy AS
Storebotn 65
5309 Kleppestø

Tel: +49 8458 32 98 0
Fax: +49 8458 32 98 30
Email: info@collomix.de
Web: www.collomix.de

Tel: +47 55 94 74 94
Epost: bestilling@askmur.no
Web: www.askmur.no

Forhandler: