



Cap

impact resistant, robust

Arrangement of motor

vertical – dust is kept away, durable

Speed regulation

adaptation of speed (EBS 125.4 RO)

Dust guard

foldable front edge to get to the edge of the working area

Brush rim

protection against dust emission

Vibration damping

splitting between motor and handle (patented) – efficient vibration absorption, protects the wrists of the user, better grinding performance

Vacuum cleaner connection

für dust extraction



FEATURES OF CONCRETE GRINDERS

The EIBENSTOCK concrete grinder sets the standards in terms of their handiness. The special parallel grip design provides the user with numerous benefits including even distribution of pressure on the disc, even overhead. The use of a vacuum cleaner with the dusthood ensures a clean working environment, but also prolongs the lifetime of the machine.



Concrete grinder EBS 1802



Ø 125



Concrete grinder EBS 1802 SH



Ø 125



The powerful hand-held grinder for small to medium sized surfaces

USE:

- Grinding and smoothing of surfaces
- Removing of screed seams, residual mud, plaster and coatings
- Preparing of surfaces, e.g. for tile renovation
- Concrete, screed, tile adhesive, plaster, paint, coatings, carpet adhesive – with corresponding grinding wheels (accessories)
- **EBS 1802 SH – the machine for every surface:** PCD-grinding wheel with monobloc diamonds – high removal rate and long lasting

FEATURES:

- Powerful motor – high capacity
- Electronic – soft start, over current cut-off, overload indication
- Foldable front edge of dust guard – for grinding directly to the edge of the work area (no laborious reworking, saves time and costs)
- Brush rim – high suction power for dust-free working by connecting an industrial vacuum cleaner (accessory) to the 35 mm nozzle
- Parallel handle position – ergonomic handling allows exact and balanced guiding for a better surface finish
- Floor guiding device – available as accessory (not for use with PCD-grinding wheels)

SPECIFICATIONS	EBS 1802
Power input	1800 W
Rated voltage	230 V ~
No-load speed	10000 rpm
Disc diameter	125 mm
Spindle connection	Ø 22.2 mm
Weight	5.9 kg
Order no.	0633J000
Supplied	in a case incl. diamond-grinding wheel (concrete) and assembly tools

SPECIFICATIONS	EBS 1802 SH
Power input	1800 W
Rated voltage	230 V ~
No-load speed	10000 rpm
Disc diameter	125 mm
Spindle connection	Ø 22.2 mm
Weight	5.9 kg
Order no.	0633L000
Supplied	in a case incl. PCD-grinding wheel (pointed segments) and assembly tools

EBS 1802 SH – the machine for every surface: PCD-grinding wheel included in delivery

