

# PLANITOP RASA E RIPARA Declaration of Performance N. CPR-IT1/0313

#### **DECLARATION OF PERFORMANCE N. CPR-IT1/0313**

- 1) Unique identification code of the product-type: PLANITOP RASA E RIPARA
- 2) Intended uses: Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods
- 3) Manufacturer: MAPEI S.p.A. Via Cafiero, 22 20158 Milan Italy www.mapei.it

4) Systems of AVCP: System 2+

System 4 (for reaction to fire)

5) Harmonized standards: EN 1504-2:2004

Notified bodies: the notified body ICMQ SpA, N. 1305, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

### 6) Performances declared:

Essential characteristics	Performances
Water vapour permeability:	Class I
Capillary absorption and permeability to water:	< 0,1 kg*m <sup>-2</sup> *h <sup>-0,5</sup>
Thermal compatibility:	
- Freeze-Thaw cycling:	≥ 1,5 N/mm²
Adhesion strength by pull-off test:	≥ 2,0 N/mm <sup>2</sup>
Reaction to fire:	Class A1
Dangerous substances:	see SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: Paolo Murelli - Corporate Quality Management

Milan, 22/01/2015

DoP in Pdf format are available in the Mapei website.

Revision 1 notes: Updating to new DoP layout

Jas Ulmel'

# PLANITOP RASA E RIPARA CE MARKING

Annex to DoP N. CPR-IT1/0313







Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it

## 10 CPR-IT1/0313 EN 1504-2:2004 PLANITOP RASA E RIPARA

Cementitious coating for intended use in concrete surface protection by moisture control and increasing resistivity methods

Water vapour permeability: Class I

Capillary absorption and permeability to water: < 0,1 kg\*m-2\*h-0,5

Thermal compatibility:

- Freeze-Thaw cycling:  $≥ 1,5 \text{ N/mm}^2$ Adhesion strength by pull-off test:  $≥ 2,0 \text{ N/mm}^2$ Reaction to fire: Class A1
Dangerous substances: see SDS

#### Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.